



The Proven Performer in Laundry

SPEED QUEEN® ON-PREMISES LAUNDRY SOLUTIONS

Stacked Washer-Extractor/Tumble Dryers

SST30

2×30 lb (13 kg)

SST50

2×50 lb (25 kg)

Maximize Time and Space

Speed Queen's stacked washer-extractor/tumble dryer is a unique product that truly delivers increased productivity.

- Ideal for small OPL settings with limited space
- Increases wash capacity
- Improves throughput
- Minimal front fasteners give quick access to key washer-extractor components to improve serviceability
- Supports a higher volume than typical retail and light commercial products are able to support
- More than double production with higher capacity and faster wash times
- Reliability and durability that drastically outperforms retail or light commercial options

 3 Year
Warranty

See Speed Queen Warranty Bond for specifics.



Stacked Washer-Extractor/Tumble Dryers

		SST30		SST50		
		Washer-Extractor	Tumble Dryer	Washer-Extractor	Tumble Dryer	
Control Option		OPL Touch		OPL Touch		
Capacity - lb (kg)		30 (13) x 2		50 (25) x 2		
Overall Width - in (mm)		31.4 (797)		34.4 (875)		
Overall Depth - in (mm)		45.5 (1152)		51.3 (1302)		
Overall Height - in (mm)		79.7 (2023)		84.3 (2141)		
Cylinder Diameter - in (mm)		24.0 (610)	30.0 (762)	26.3 (668)	33.0 (838)	
Cylinder Depth - in (mm)		16.0 (406)	26.0 (660)	20.3 (515)	30.0 (762)	
Cylinder Volume - cu. ft (liters)		4.2 (119)	10.6 (300)	6.3 (178)	14.8 (419)	
Reversing Cylinder		-	Standard	-	Standard	
Door Opening Size - in (mm)		14.3 (363)	22.6 (574)	16.3 (414)	26.9 (683)	
Door Bottom to Floor - in (mm)		14.0 (356)	51.3 (1303)	14.6 (370)	52.3 (1328)	
Water Inlet Connection - in (mm)		2 x 0.75 (19)	-	2 x 0.75 (19)	-	
Drain Diameter - in (mm)		1 x 3 (76)	-	1 x 3 (76)	-	
Drain Height to Floor - in (mm)		4.3 (108)	-	4.5 (115)	-	
Heat Input Power - Btu/hr (kW, Mj/hr.)		-	73,000 (21.4, 77.0)	-	95,000 (27.8, 100)	
Gas Connection - in		-	1/2 NPT	-	1/2 NPT	
Air Outlet - in (mm)		-	8.0 (200) Elliptical	-	10.0 (250) Elliptical	
Airflow - cfm (l/sec)		-	400 (190)	-	600 (285)	
Motor - HP (kW)	Fan	-	0.5 (0.4)	-	0.5 (0.4)	
	Drive	1 (0.75)	0.3 (0.2)	2 (1.5)	0.5 (0.4)	
Total # of Speeds		6	-	6	-	
Cylinder Speeds - RPM (G-Force)	Gentle	34 (0.4)	-	33 (0.4)	-	
	Wash	48 (0.8)	-	46 (0.8)	-	
	Distribution	86 (2.5)	-	82 (2.5)	-	
	Very Low	282 (27)	-	269 (27)	-	
	Low	485 (80)	-	464 (80)	-	
	Medium	542 (100)	-	518 (100)	-	
Electrical Specs - amps	Gas					
	X	200-240V/50/60/1/3	15	10	15	10
	B	100-120V/50/60/1	15	15	-	-
	Electric					
	D	200-208V/50/60/1	15	60	-	-
	E	230-240V/50/60/1	15	50	-	-
	F	200-208V/50/60/3	15	80	-	-
G	230-240V/50/60/3	15	70	-	-	
Shipping Dimensions Approx. - in (mm)	Width	34.5 (876)		35.5 (902)		
	Depth	47.0 (1194)		54.0 (1372)		
	Height	83.0 (2108)		89.0 (2261)		
Net Weight - lb (kg)		770 (349)		910 (413)		
Shipping Weight - lb (kg)		787 (357)		930 (422)		
Agency Approvals		UL _{us}	CSA	UL _{us}	CSA	

For the most accurate information, the installation guide should be used for all design and construction purposes.
 Due to continuous product improvements, design and specifications subject to change without notice.
 The quality management systems at Alliance Laundry Systems are registered to ISO 9001.